

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/002,576	10/26/2001	Changmin Chun	ECB-0115	4233
27810	7590 05/25/2004		EXAMINER	
EXXONMOBIL RESEARCH AND ENGINEERING COMPANY			WILKINS III, HARRY D	
P.O. BOX 90 1545 ROUTE			ART UNIT	PAPER NUMBER
	E, NJ 08801-0900		1742	-
			DATE MAIL ED: 05/25/200	4

Please find below and/or attached an Office communication concerning this application or proceeding.

		Application No.	Applicant(s)		
		10/002,576	CHUN ET AL.		
	Office Action Summary	Examiner	Art Unit		
		Harry D Wilkins, III	1742		
Period fo	The MAILING DATE of this communication app	ears on the cover sheet with the c	orrespondence address		
A SH THE - Exte after - If the - If NC - Failu Any	ORTENED STATUTORY PERIOD FOR REPLY MAILING DATE OF THIS COMMUNICATION. nsions of time may be available under the provisions of 37 CFR 1.13 SIX (6) MONTHS from the mailing date of this communication. e period for reply specified above is less than thirty (30) days, a reply operiod for reply is specified above, the maximum statutory period we are to reply within the set or extended period for reply will, by statute, reply received by the Office later than three months after the mailing ed patent term adjustment. See 37 CFR 1.704(b).	66(a). In no event, however, may a reply be time within the statutory minimum of thirty (30) days ill apply and will expire SIX (6) MONTHS from cause the application to become ABANDONEI	ely filed will be considered timely. the mailing date of this communication. O (35 U.S.C. § 133).		
Status					
1)⊠	Responsive to communication(s) filed on 15 Ag	<u>oril 2004</u> .			
2a)⊠	This action is FINAL . 2b) This action is non-final.				
3)□	Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under <i>Ex parte Quayle</i> , 1935 C.D. 11, 453 O.G. 213.				
Disposit	ion of Claims				
5)□	Claim(s) 1,2,6,7,10 and 11 is/are pending in the application. 4a) Of the above claim(s) is/are withdrawn from consideration. Claim(s) is/are allowed. Claim(s) 1,2,6,7,10 and 11 is/are rejected. Claim(s) is/are objected to.				
Applicat	ion Papers				
10)⊠	The specification is objected to by the Examiner The drawing(s) filed on <u>26 October 2001</u> is/are: Applicant may not request that any objection to the Replacement drawing sheet(s) including the correction The oath or declaration is objected to by the Ex	a)⊠ accepted or b)⊡ objected drawing(s) be held in abeyance. See on is required if the drawing(s) is obj	37 CFR 1.85(a). ected to. See 37 CFR 1.121(d).		
Priority (ınder 35 U.S.C. § 119				
a)	Acknowledgment is made of a claim for foreign All b) Some * c) None of: 1. Certified copies of the priority documents 2. Certified copies of the priority documents 3. Copies of the certified copies of the prior application from the International Bureau See the attached detailed Office action for a list of	s have been received. s have been received in Application ity documents have been received (PCT Rule 17.2(a)).	on No d in this National Stage		
Attachmen		_			
	e of References Cited (PTO-892) e of Draftsperson's Patent Drawing Review (PTO-948)	4) 🔲 Interview Summary (Paper No(s)/Mail Da			
3) 🔲 Infori	re of Drantsperson's Patent Drawing Review (PTO-948) mation Disclosure Statement(s) (PTO-1449 or PTO/SB/08) r No(s)/Mail Date		te atent Application (PTO-152)		

Art Unit: 1742

DETAILED ACTION

Claim Rejections - 35 USC § 103

- 1. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:
 - (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.
- 2. Claims 1, 2, 7 and 10 are rejected under 35 U.S.C. 103(a) as being unpatentable over Ramanarayanan et al (US 5,869,195) in view of Applicant's admission of prior art, Garg et al (US 6,287,393) and Hemsath et al (US 5,997,286).

Ramanarayanan et al teach a method where a pearlitic surface layer is formed on a steel article. Ramanarayanan et al teach (see col 2, line 66 to col 3, line 12) that a surface layer of at least 1 micron is transformed by conventional carburizing methods. The method includes (equivalent to (c) of present invention) slow cooling from the carburizing treatment in order to form the pearlite microstructure. Ramanarayanan et al teach (see col 3, lines 9-12) that when the surface pearlite was formed, only the surface layer was required to have more than 0.7 wt% C. Thus, the bulk alloy (i.e.-precarburized) of Ramanarayanan et al contains less than 0.7 wt% C.

Ramanarayanan et al do not teach the claimed method of carburizing of (a) heating to the austenite region and (b) exposing to a supersaturated carbon environment at 727-900°C.

Garg et al teach (see col 5, lines 24-46 and col. 9, lines 38-64) a method of carburizing steel that includes (a) heating at 750-950°C and (b) exposing the steel to a

Art Unit: 1742

carburizing atmosphere containing CO and H_2 . The atmosphere can contain as much as 50 vol% CO (where n=1 and m=0, both within the range of Garg et al), with no N_2 added, thus leaving the other 50 vol% to be essentially all H_2 . There would be some residual methane and/or CO_2 in the atmosphere, but not enough to affect the carburizing. Thus, the atmosphere composition taught by Garg et al consists essentially of CO and H_2 . Though Garg et al do not contain any express teachings regarding the saturation or carbon activity of the atmosphere, one of ordinary skill in the art would have expected that with the 50/50 CO/H_2 atmosphere, the carbon activity would have been increased, thereby creating a supersaturated environment, because more carbon in the atmosphere (higher carbon activity) increases the rate of carbon transfer to the iron and also increases the maximum carbon content of the iron (for support, see "Gas Carburizing").

Therefore, it would have been obvious to one of ordinary skill in the art to have performed the conventional heating and carburizing steps as taught by Garg et al as the carburizing treatment of Ramanarayanan et al because the CO/H₂ environment of Garg et al is effective at quickly facilitating carbon transfer to the steel (see Garg et al at col 7, lines 5-24).

Garg et al teach (see col. 5, lines 32-35) that the process of carburizing is carried out at 750-950°C in a batch or continuous furnace in the presence of a carburizing atmosphere. However, Garg et al does not expressly teach when the steel article is exposed to the carburizing atmosphere.

Art Unit: 1742

Hemsath et al teach (see abstract and col. 6, lines 48-62) that a continuous furnace for carburizing articles includes a separate preheating zone for deoiling of the article and a carburizing zone where the carburizing atmosphere is introduced to the preheated article.

Therefore, it would have been obvious to one of ordinary skill in the art to have performed a preheating step as taught by Hemsath et al prior to exposing the article to the carburizing atmosphere of Garg et al because the preheating allows for the article to be deoiled (i.e.-cleaned). The preheating (to the temperature of carburizing) would inherently convert portions of the ferrite to austenite because the temperature at which ferrite starts to convert to austenite is 723°C and the heating is to a temperature of 750-950°C.

Ramanarayanan et al further teach that an FeS surface layer is formed on top of the pearlite layer in order to add corrosion resistance to acids. However, Applicant admits as prior art (see paragraph 3) that pearlite was known to be resistant to corrosion by organic acids. Therefore, the FeS layer of Ramanarayanan et al is not needed as the pearlite layer provides sufficient corrosion resistance for certain environments.

Regarding claim 2, Ramanarayanan et al teach (see col 2, lines 49-52) that preferred steels include 0.6-0.9 wt% Mn and 0.1-0.5 wt% Si.

Regarding claims 7 and 10, Ramanarayanan et al teach (see col 1, lines 41-42) that the thickness of the pearlitic region is preferably at least 20 microns. As can be seen from Figs. 1B and 1C of Ramanarayanan et al, the layer of pearlite is continuous.

Art Unit: 1742

3. Claims 6 and 11 are rejected under 35 U.S.C. 103(a) as being unpatentable over Ramanarayanan et al (US 5,869,195) in view of Applicant's admission of prior art, Garg et al (US 6,287,393) and Hemsath et al (US 5,997,286) as applied to claims 1, 2 and 7 above, and further in view of Kerridge (US 4,461,655).

Ramanarayanan et al, Applicant's admission, Garg et al and Hemsath et al do not teach that the carburizing time was about 1 minute to about 50 hours as claimed.

Kerridge teaches that treatment time affects carburized depth (see col 3, lines 22-27).

Therefore, it would have been within the expected skill of a routineer in the art to have optimized the time of treatment in order to adjust the depth of the carburized layer that forms pearlite upon slow cooling because Kerridge teaches that treatment time affects carburized depth (see col 3, lines 22-27).

Regarding claim 11, it would have been within the expected skill of a routineer in the art to have performed the carburization for a length of time sufficient to convert the entire iron article to pearlite.

Response to Arguments

- 4. Applicant's arguments filed 15 April 2004 have been fully considered but they are not persuasive. Applicant argued that:
 - a. Ramanarayanan et al are teaching that what is being converted to pearlite must have greater than 0.7 wt%.

In response, the Examiner agrees. However, this still overlaps the presently claimed range of less than 0.77 wt%.

Art Unit: 1742

b. That Ramanarayanan et al teaches only the surface need have greater
 than 0.7 wt% C is a statement taken out of context in an attempt to render
 Applicant's invention obvious.

In response, please see col. 3, lines 9-12 of Ramanarayanan et al to rebut this argument.

- c. Garg et al fail to teach carburizing a steel with less than 0.77 wt% C.

 In response, Garg et al do not teach anything about the product to be carburized.

 Thus, while one of ordinary skill in the art would have expected that the carburizing atmosphere could be used with any steel that can be carburized.
 - d. Hemsath et al do not teach a sufficient pre-heat temperature to cause austenization.

In response, while Hemsath et al teach a temperature of 800°F for the preheat zone, the carburization occurs at 1350°F (732°C). It would have been within the expected skill of a routineer in the art to have adjusted the preheat temperature based upon the carburization temperature in the process of Ramanarayanan et al.

Conclusion

5. Applicant's amendment necessitated the new ground(s) of rejection presented in this Office action. Accordingly, **THIS ACTION IS MADE FINAL**. See MPEP § 706.07(a). Applicant is reminded of the extension of time policy as set forth in 37 CFR 1.136(a).

A shortened statutory period for reply to this final action is set to expire THREE MONTHS from the mailing date of this action. In the event a first reply is filed within

Art Unit: 1742

TWO MONTHS of the mailing date of this final action and the advisory action is not mailed until after the end of the THREE-MONTH shortened statutory period, then the shortened statutory period will expire on the date the advisory action is mailed, and any extension fee pursuant to 37 CFR 1.136(a) will be calculated from the mailing date of the advisory action. In no event, however, will the statutory period for reply expire later than SIX MONTHS from the date of this final action.

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Harry D Wilkins, III whose telephone number is 571-272-1251. The examiner can normally be reached on M-Th 10:30am-9:00pm.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Roy V King can be reached on 571-272-1244. The fax phone number for the organization where this application or proceeding is assigned is 703-872-9306.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

Harry D Wilkins, III Examiner Art Unit 1742

hdw

ROY KING
SUPERVISORY PATENT EXAMINER
TECHNGLOGY CENTER 1700